

**Device Characteristics**

Configuration	Port Identification	Fiber Type	Notes
Signal input port		12/250 um NA=0.08/0.46	

**Optical Performance Specifications**

Parameters	Min.	Typ.	Max.	Units	PDR	Notes
Central Wavelength	1079.00	1080.00	1081.00	nm	Yes	1,2,3
FWHM (-3dB)	1.80	2.00	2.20	nm	Yes	
Reflectivity	99.5			%	Yes	4
Wavelength matching			0.20	nm	Yes	
Power handling (CW Signal)			500	W		5
Power handling (CW Pump)			1000	W		5

**Mechanical and Environmental Specifications**

Parameters	Value	Notes
Pigtail length	>1 m - Recoat Center - >1 m	
Recoating	Low index Polymer	

**Additional Informations / Customer requirements**

Blue and black marks on short wavelength side

Wavelength matching with FBGL2ELC9799

**Note(s)**

- [1] Specified at nominal operating temperature : 22°C
- [2] Optical spectrum analyser referenced to vacuum
- [3] If a polarization maintaining (PM) fiber is used, the measurement is performed along the slow axis
- [4] LP01's peak reflectivity is estimated from the measured transmission spectrum
- [5] Heatsinking is required

This part is considered under development  
 Specification subject to change without notice.  
 Made in Canada